



## **Conti HAC 3** Intelligent Construction All-Position

Applications: Wide base, all-position fitment for on/off, mixed service applications.



Conti HAC 3

			ISTRUCTION
_egend:			
3 <b>@</b>		ಿ	O
3G Casing	SmartWay <sup>®</sup> Verified	Intelligent Tire	Retread Available

Conti HAC 3 **Intelligent Construction All-Position** 







64

## PRODUCT DATA

	LOAD RANGE	ARTICLE	TREAD DEPTH (32nds)		STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOA INFLATIC SINGLE	
					IN	мм	IN	мм	IN	мм	IN	мм		IN	мм	мі	КМ	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
385/65R22.5	L	¢05652000000\$	22	68	19.6	498	42.0	1067	14.8	376	15.9	404	11.75, 12.25	N/A	N/A	493	306	171	78	9920, 130 (4500, 900)	N/A
425/65R22.5	L	♦05652010000	24	68	20.8	529	44.8	1138	16.6	421	17.9	454	13.00, 12.25, 14.00	N/A	N/A	462	287	190	86	11400, 120 (5150, 830)	N/A
445/65R22.5	М	*05652020000*	23	68	20.9	531	45.2	1148	17.4	442	18.6	472	13.00, 14.00	N/A	N/A	458	285	210	95	12800, 130 (5800, 900)	N/A

Note - Rim listed first is the measuring rim. 11 = Intelligent Tire Article #. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturer load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

## Features & Benefits



Aggressive on/off-road tread design combined with enhanced cap/base compounds for improved mileage and traction.

(CONNECT



Rugged 4-belt tread package resists impacts, bruises and penetrations for improved casing durability.

**Continental's Intelligent Tire** 

• Equipped with TPMS Sensor for accurate, realtime tire pressure and temperature readings.

 Sensor provides true casing temperature allowing preventive actions that make your tire last longer. • Avoids valve damage and air leaks by mounting

Learn more at www.continental-truck.com.

Sensor warrantied for 5 Years to

See warranty policy for details.

minimize disruptions.

on the inner liner.



Minimal stone retention due to self-cleaning tread pattern and groove geometry for enhanced retreadability.



Increased sidewall gauge for improved resistance against curbing, cuts and abrasions.



This product is Mud + Snow Certified.

Applications: Wide base, all-position fitment for on/off-road, mixed service applications such as cement mixers.