

Conti HDC 3 Intelligent Construction Drive

Applications: Construction, coal haulers, logging, waste haulers and other on/off highway service.









TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
																				SINGLE	DUAL
	10.0102				IN	ММ	IN	ММ	IN	ММ	IN	ММ	itiii(3)	IN	ММ	МІ	КМ	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
11R22.5	R22.5 H	* 05652410000 *	30	68	19.9	504	42.1	1069	11.7	298	12.7	322	8.25, 7.50	12.5	318	492	306	143	65		6005, 120
																				(3000, 830)	(2725, 830)
11R24.5	Н	* 05652430000 *	30	68	20.7	526	44.1	1120	11.7	298	12.8	324	8.25, 7.50	12.5	318	469	292	153	69	7160, 120	6610, 120
	''				20.7															(3250, 830)	(3000, 830)
						THE	EI ECC	TIDES O	NI 1E F	CDE	DDOL	CENT	ED DIMC								

Note - Rim listed first is the measuring rim. ** = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.


Features & Renefits



Wide, aggressive open shoulder tread design with enhanced cap/base compounds for **improved mileage and traction**.



Diamond shaped lugs and optimal void volume for excellent traction.



Self-cleaning tread design and miniature stone bumpers reduce stone retention for enhanced retreadability.



Maximum sidewall protection for improved resistance against curbing, cuts and abrasions.

((CONNECT Continental's Intelligent Tire



- Equipped with TPMS Sensor for accurate, realtime tire pressure and temperature readings.
- Sensor warrantied for 5 Years to minimize disruptions.
- Sensor provides true casing temperature allowing preventive actions that make your tire last longer.
- Avoids valve damage and air leaks by mounting on the inner liner.

Learn more at www.continental-truck.com. See warranty policy for details.



Applications: Construction, coal haulers, logging, waste haulers and other on/off-road service.