





✓ GOODS ● PEOPLE ● CONSTRUCTION

HDL2+

Fuel-Efficient, Long Haul Drive



| PRODUCT DATA 3G 20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | | | | | | | | | | | | | | | 60 | | | | | | |
|--|---------------|------------------------------|---------------------------|----|----------------------------|-----|---------------------------------|------|------------------------------|-----|----------------------------|-----|--------------------|----------------------------|-----------|------------------|-----|----------------|----|-----------------------------------|--------------------------|
| TIRE SIZE | LOAD RANGE | | TREAD DEPTH (32nds) | 1 | STATIC LOADED RADIUS | | OVERALL INFLATED DIAMETER | | OVERALL INFLATED WIDTH | | LOADED SECTION WIDTH | | APPROVED RIM(S) | MINIMUM DUAL SPACING | | REVS PER UNIT | | TIRE WEIGHT | | MAX. LOAD @ INFLATION SINGLE DUAL | |
| | | | | | IN | ММ | IN | ММ | IN | ММ | IN | ММ | KiiiKS | IN | ММ | MI | КМ | LB | KG | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |
| 295/75R22.5 | G | 05211950000 *05653940000* | 26 | 75 | 18.9 | 481 | 40.5 | 1029 | 11.5 | 292 | 12.9 | 328 | 8.25, 9.00 | 12.5 | 318 | 511 | 318 | 120 | 54 | 6175, 110 (2800, 760) | 5675, 110 (2575, 760) |
| 295/75R22.5 | Н | 05211960000 *05653930000* | 26 | 75 | 18.9 | 481 | 40.5 | 1029 | 11.5 | 292 | 12.9 | 328 | 8.25, 9.00 | 12.5 | 318 | 511 | 318 | 122 | 55 | 6610, 120 (3000, 830) | 6005, 120 (2725, 830) |

Note - Rim listed first is the measuring rim. 👀 = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains...# - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

Features & Benefits



Advanced tread compounding for maximum fuel efficiency,



innovative groove geometry minimizes stone retention.



Built on the Conti 3G Casing for maximum retreadability.

Applications: Long haul over the road drive positions.