






HDL₂

Fuel-Efficient, Long Haul Drive





✓ GOODS ● PEOPLE ● CONSTRUCTION

PRODUCT DATA






| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32nds) | MAX SPEED (MPH) | STATIC LOADED RADIUS | | OVERALL INFLATED DIAMETER | | OVERALL INFLATED WIDTH | | LOADED SECTION WIDTH | | APPROVED RIM(S) | MINIMUM DUAL SPACING | | REVS PER UNIT | | TIRE WEIGHT | | MAX. LOAD | @ INFLATION |
|--------------|---------------|------------------------------------|---------------------------|-----------------------|----------------------------|-----|---------------------------------|---------|------------------------------|-------|----------------------------|-------|--------------------|----------------------------|-----|------------------|-----|----------------|----|--------------------------|--------------------------|
| | | | | | | | | | | | | | | | | | | | | SINGLE | DUAL |
| | | | | | IN | ММ | IN | ММ | IN | мм | IN | мм | iiiii(3) | IN | ММ | MI | КМ | LB | KG | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |
| 11R22.5 | G | 05211220000 *05651770000 | 26 | 75 | 19.6 | 499 | 42.0 | 1066 | 11.7 | 296 | 13.1 | 331 | 8.25, 7.50 | 12.5 | 318 | 493 | 306 | 125 | 57 | 6175, 105 (2800, 720) | 5840, 105 (2650, 720) |
| 11R22.5 | Н | 05211230000 *05652990000* | 26 | 75 | 19.6 | 499 | 42.0 | 1066 | 11.7 | 296 | 13.1 | 331 | 8.25, 7.50 | 12.5 | 318 | 493 | 306 | 128 | 58 | 6610, 120 (3000, 830) | 6005, 120 (2725, 830) |
| 11R24.5 | G | 05211240000 | 26 | 75 | 20.5 | 521 | 44.0 | 1118 | 11.7 | 296 | 13.1 | 331 | 8.25, 7.50 | 12.5 | 318 | 470 | 292 | 134 | 61 | 6610, 105 (3000, 720) | 6005, 105 (2725, 720) |
| | | | | | | TL | JBELES | S TIRES | ON 15 | DEGRE | E DRC | P CEN | TER RIMS | | | | | | | | |

Note - Rim listed first is the measuring rim. 0 = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

Features & Benefits



Advanced tread compounding for maximum fuel efficiency.



Innovative groove geometry minimizes stone retention.



Built on the **Conti 3G Casing** for maximum retreadability.

Applications: Long haul over the road drive positions.