





HDR+

19.5" Regional Drive





⋖ GOODS **⋖** PEOPLE **⋖** CONSTRUCTION

PRODUCT DATA



	TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
																					SINGLE	DUAL
						IN	ММ	IN	ММ	IN	ММ	IN	ММ	Talling)	IN	MM	MI	КМ	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
	225/7OR19.5*	G	05224030000 * 05652870000 *	18	87	15.1	384	32.2	819	8.7	221	9.4	238	6.00, 6.75	10.0	254	642	399	63	29	3970, 110 (1800, 760)	3750, 110 (1700, 760)
	225/70R19.5*	Н	05224040000 * 05652880000 *	18	87	15.2	385	32.2	818	8.7	221	9.4	239	6.75	10.0	254	643	399	65	29	4190, 120 (1900, 830)	3970, 120 (1800, 830)
	223/101113.3		05652880000 ♦	10		.5.2								TED DIMS	10.0	231	0 15	333	- 55	23	(1900, 830)	(180

Note - Rim listed first is the measuring rim. • • = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. • - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change O1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturers.

Features & Benefits



Improved cap/base tread compound for increased removal miles and resistance to tears.



18/32" tread pattern provides excellent traction and long mileage in regional and local service.



Aggressive tread design provides excellent lateral stability to minimize squirm and improve handling.



Open shoulder tread pattern with tie-bar provides even tread wear along with reduced noise and improved traction.



Mileage Improvement vs. HDR

HDR+ delivers 13% improvement in removal miles vs. HDR.

Applications: Regional hauling and on/off road, drive position.