



Your mission. Our strength.

Continental Military Tires



Off-road and always on track. We make missions possible.

There's no such thing as difficult terrain. Just the wrong choice of tires.

Tough tracks call for special tires. Our Special Off-Road Tires are always deployed whenever conventional tires can't get the job done. In difficult situations, our tires perform for you - whether off-road tracks, the roughest terrain, in soft sand or roads pitted with potholes. Our tires leave no one stranded - since when the roads become rough, you cannot afford any breakdowns.

Our Special Off-Road Tires are designed to meet any challenge a demanding driving mission might encounter. Soft ground requires precision traction, while rough terrain calls for an extremely robust design that renders cuts in the tire virtually impossible. This is why we carry the right tire no matter how difficult the terrain. Our mission statement reads as follows: Conquer any terrain at the highest possible speed, while still ensuring maximum durability of the tires.

Thanks to a sophisticated combination of a high-performance truck tire and a heavy-duty industrial tire, we have developed our Special Off-Road Tires, which excel in the most extreme situations. Power, efficiency, speed and endurance always come first in difficult terrains. Special Operation tires give you an extra advantage in the field.



Product features determine performance.

The overview outlines which technical attributes directly contribute to achieve specific performance requirements.

Durability

Belts

The reinforced belt package ensure the stiffness of the overall structure and protects the casing effectively

Carcass

The robustness of the carcass provides optimal impact protection

Compound

The toughness of the new on-/off-road compound reduces the number and most importantly the depth of cuts and tears

Traction

Tread

Greater depth, more volume and an optimized tread design ensures reliable grip both on and off the road

Contour

Optimized footprint enabling the maximum contact area

Inflation

Wide ranges of operating inflation pressure enable continuous vehicle operation in both on and off the road environments

Endurance

Compound

Low heat build up properties maximizing mobility both on and off the road

Belts

Reinforced belt package withstands highly concentrated pressure and prevents fatigue fractures

Carcass

Reinforced casing provides greater load carrying capacity

Performance Overview



MPT 80 POR

10.5 R 20 MPT 134J

12.5 R 20 MPT 147J

14.5 R 20 MPT 152J



MPT 81 / MPT 81M* POR

275/80 R 20 MPT (134K)

315/55 R 16 MPT (120K/124F)

335/80 R 20 MPT (147K)

365/80 R 20 MPT (152K)

365/80 R 20 MPT (152K)*

MPT 91 POR

275/80 R 20 MPT (137/135K)

335/80 R 20 MPT (150K)**

365/80 R 20 MPT (158K)**



SOT

415/80 R 685 (168K)

325/85 R 16 (140K) POR **

255/100 R 16 (126K) POR **



HCS / SOT POR

14.00 R 20 (164K)

14.00 R 20 (168K)**

16.00 R 20 (173G)

365/85 R 20 (164J)

395/85 R 20 (168J)

395/85 R 20 (168K)**

* On demand

** In preparation



Sand

Road

Cross Country

Mud

MPT 80

MPT 81 / MPT 91

SOT

HCS / SOT

Technical Data

Tire Size	Pattern	LI / SSY	TT/TL	M&S	POR	Tread depth in mm	Dual spacing in mm	Appr. weight in kg	Rim
255/100 R 16 **	SOT	126 K	TL	yes	yes	in preparation			6.50H-16
315/55 R 16 MPT	MPT81	120K/124F	TL	yes	yes	16,5	-	29,5	W10Lx16
									10LBx16
									11x16
325/85 R 16 **	SOT	140 K	TL	yes	yes	in preparation			9.00-16
10.5 R 20 MPT	MPT80	134 J	TL	yes	yes	16,5	-	39,0	8x20
									9x20
									10x20
275/80 R 20 MPT	MPT81	134 K	TL	yes	yes	16,5	-	39,8	9x20
									9-20SDC
									W9x20
275/80 R 20 MPT **	MPT91	137/135 K	TL	yes	yes	16,5	205	44,6	9x20
									9-20SDC
									W9x20
12.5 R 20 MPT	MPT80	147 J	TL	yes	yes	16,5	-	52,5	11x20
									11-20SDC
									9x20
335/80 R 20 MPT	MPT81	147 K	TL	yes	yes	16,5	-	52,1	10x20
									11x20, 11-20SDC
									9x20
335/80 R 20 MPT **	MPT91	150 K	TL	yes	yes	in preparation			10x20
									11x20, 11-20SDC
									9x20
14.5 R 20 MPT	MPT80	152 J	TL	yes	yes	17,5	-	62,5	11x20
									11-20SDC
									12-20SDC
365/80 R 20 MPT	MPT81	152 K	TL	yes	yes	19,5	-	73,1	11x20
									11-20SDC
									12-20SDC
365/80 R 20 MPT	MPT81 M*	152 K	TL	yes	yes	19,5	-	76,5	11x20
									11-20SDC
									12-20SDC
365/80 R 20 MPT **	MPT91	158 K	TL	yes	yes	19,5	-	74,7	11x20
									11-20SDC
14.00 R 20	HCS	164 K	TL	yes	yes	20,1	-	103,5	10.00
14.00 R 20	HCS	168 K **	TL	yes	yes	20,1	-	104.3	10.00
365/85 R 20	HCS	164 J	TL	yes	yes	21,0	-	90,1	10.00
395/85 R 20	HCS	168 J	TL	yes	yes	23,9	-	104,5	10.00
395/85 R 20	HCS	168 K**	TL	yes	yes	23,9	-	104,5	10.00
16.00 R 20	SOT	173 G	TL	yes	yes	27,0	-	147,0	10.00 W – 20
415/80 R 685 TR	SOT	168 K	TL	yes	no	19,5	-	118	230-685 TR

Construction and off-road tires, including Professional Off-Road (POR) Tires, are primarily engineered for use in off-road environments. These tires are not intended for sustained high-speed operation on highway or similar paved roads, as such usage may result in excessive heat buildup and premature tire failure. The information provided in this document has no legal effect and is provided exclusively for informational purposes. Liability for the information provided here is excluded. For detailed legal information please see detailed information at Continental website

Tire dimensions in mm				Load capacity depending on application						
Width	Outer diameter	Stat. radius	Rolling circum- ference	Max. load per tire in kg	Road		Cross country		Mud and sand	
					Min. infl. pressure in bar	Max. speed in km/h	Min. infl. pressure in bar	Max. speed in km/h	Min. infl. pressure in bar	Max. speed in km/h
in preparation				1700	5,25	110	3,8	70	3,0	30
329	750	344	2260	1400	4,0	110	3,2	70	2,1	30
329										
339										
in preparation				2500	5,0	110	3,6	70	2,8	30
255	950	444	2865	2120	5,25	100	4,3	70	2,7	30
265										
275										
267	950	440	2850	2120	5,25	110	4,3	70	2,7	30
267										
267										
270	950	440	2850	2300	5,5	110	4,5	70	2,9	30
270										
270										
320	1030	480	3120	3075	6,5	100	5,3	70	3,4	30
320										
334										
344	1032	480	3120	3075	6,5	110	5,3	70	3,4	30
354										
in preparation				3350	6,5	110	5,3	70	3,4	30
352	1090	503	3285	3550	6,0	100	4,9	70	3,1	30
352										
362										
380	1091	502	3275	3550	6,0	110	4,9	70	3,1	30
380										
390										
380	1089	502	3275	3550	6,0	110	4,9	70	3,1	30
380										
390										
373	1091	499	3276	4250	6,5	110	5,3	70	3,4	30
373										
377	1251	579	3834	5000	7,5	110	6,1	70	3,9	30
377	1251	579	3834	5600	9,0	110	7,3	70	4,7	30
372	1146	524	3503	5000	8,0	100	6,5	70	4,2	30
391	1190	546	3647	5600	8,5	100	6,9	70	4,4	30
391	1190	546	3647	5600	8,5	110	6,9	70	4,4	30
432	1350	610	3830	6500	7,6	90	5,6	70	4,5	30
412	1329	616	3990	5600	8,5	110	6,9	70	4,4	30

* on demand
** in preparation

Continental Reifen Deutschland GmbH

Commercial Specialty Tires

Continental-Plaza 1, 30175 Hannover, Germany

Phone: +49 511 938 - 01

www.continental-tires.com