



Long Removal Mileage // Cut/Chip Resistance // Resistance to High Scrub // Robust Casing Construction

# Regional

## For Highway & Local Driving

**Engineered for your application.** Tires for Regional use are designed for applications where vehicles spend the majority of their time on pavement with multiple stops through inter-city operations, and mostly paved roads. Tires are optimized for high scrub, cut-chip resistance applications, as well as traction.

**IMPORTANT NOTE:** Tire Products are now classified by route. Product details are subject to change, please visit our website or contact your local sales representative for the most up to date information.

# Regional

## Truck Tire Product Overview

Legend:

|                              |                       |
|------------------------------|-----------------------|
| <b>3G</b><br>3G Casing       | SmartWay® Verified    |
| Intelligent Tire             | Retread Available     |
| <b>EV</b> ✓<br>EV Compatible | Other Sizes Available |

### Steer / All-Position



**Conti HSR 3**  
3G

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 11R22.5     | G          | 23            |
| 11R22.5     | H          | 23            |
| 12R22.5     | H          | 23            |
| 295/75R22.5 | H          | 23            |
| 11R24.5     | H          | 23            |
| 285/75R24.5 | H          | 23            |



**HSR2**

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 10R22.5     | G          | 20            |
| 11R22.5     | G          | 23            |
| 11R22.5     | H          | 23            |
| 12R22.5     | H          | 23            |
| 275/80R22.5 | H          | 23            |
| 11R24.5     | H          | 23            |
| 285/75R24.5 | H          | 23            |



**HSR2 SA**

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 255/70R22.5 | H          | 18            |
| 275/70R22.5 | J          | 18            |
| 315/80R22.5 | L          | 19            |



**HTR2**

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 385/65R22.5 | L          | 21            |
| 425/65R22.5 | L          | 22            |

### Drive Position



**HDR2+**  
3G

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 10R22.5     | G          | 24            |
| 11R22.5     | G          | 30            |
| 11R22.5     | H          | 30            |
| 12R22.5     | H          | 30            |
| 295/75R22.5 | G          | 30            |
| 295/75R22.5 | H          | 30            |
| 11R24.5     | H          | 30            |



**HDW2**  
3G

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 11R22.5     | H          | 27            |
| 11R24.5     | H          | 27            |
| 295/75R22.5 | H          | 27            |



**Conti Scandinavia HD3**  
3G

| TIRE SIZE | LOAD RANGE | DEPTH (32nds) |
|-----------|------------|---------------|
| 11R22.5   | H          | 27            |
| 11R24.5   | H          | 27            |



**HDR**

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 255/70R22.5 | H          | 26            |



# Regional

## Truck Tire Product Overview (Continued)

Legend:



3G Casing



SmartWay® Verified



Intelligent Tire



Retread Available



EV Compatible



Other Sizes Available

### Trailer Position



Conti Hybrid HT3



| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 11R22.5     | G          | 16            |
| 11R22.5     | H          | 16            |
| 255/70R22.5 | H          | 16            |
| 295/75R22.5 | G          | 16            |
| 11R24.5     | G          | 16            |
| 285/75R24.5 | H          | 16            |



HTR2 (17.5")

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 215/75R17.5 | H          | 16            |
| 235/75R17.5 | H          | 16            |

### 17.5" Tires



Conti LAR 3

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| LT215/85R16 | E          | 14            |
| LT225/75R16 | E          | 14            |
| LT235/85R16 | E          | 14            |
| LT245/75R16 | E          | 14            |



LSR1



| TIRE SIZE | LOAD RANGE | DEPTH (32nds) |
|-----------|------------|---------------|
| 10R17.5   | H          | 17            |

### 19.5" Tires



Conti Hybrid HS3 (19.5")

| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 245/70R19.5 | G          | 16            |
| 245/70R19.5 | H          | 16            |
| 265/70R19.5 | G          | 17            |
| 285/70R19.5 | H          | 18            |

\*All-Position

### 19.5" Tires (continued)



Conti HSR 5 (19.5")



| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 225/70R19.5 | G          | 16            |
| 225/70R19.5 | H          | 16            |



Conti Hybrid HD3 (19.5")

| TIRE SIZE             | LOAD RANGE | DEPTH (32nds) |
|-----------------------|------------|---------------|
| 245/70R19.5           | G          | 19            |
| 245/70R19.5           | H          | 19            |
| 265/70R19.5 (Tread B) | G          | 20            |
| 285/70R19.5 (Tread B) | H          | 20            |

\*Drive Position



Conti HDR 5 (19.5")



| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 225/70R19.5 | G          | 16            |
| 225/70R19.5 | H          | 16            |



Conti Scandinavia HD3 (19.5")



| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 225/70R19.5 | G          | 19            |
| 245/70R19.5 | H          | 21            |

\*Drive Position



Conti Hybrid HT3 (19.5")



| TIRE SIZE   | LOAD RANGE | DEPTH (32nds) |
|-------------|------------|---------------|
| 265/70R19.5 | H          | 17            |
| 285/70R19.5 | J          | 18            |

\*Trailer Position

### All-Position



**HSR 5 - 19.5"**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 200           | 16               |
| 210           | 16               |



**HSR 3**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 190           | 20               |
| 200           | 20               |
| 210           | 20               |
| 220           | 20               |
| 230           | 20               |
| 240           | 20               |



**HSR**

| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 195           | 18               |
| 215           | 18               |
| 225           | 18               |
| 235           | 18               |
| 260           | 18               |



**LSR1**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 160           | 15               |
| 180           | 15               |
| 188           | 15               |
| 195           | 15               |
| 205           | 15               |

### Drive Position



**HDR 5 - 19.5"**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 200           | 22               |
| 210           | 22               |
| 220           | 22               |



**HDR2**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 185           | 22               |
| 195           | 22               |
| 215           | 26               |
| 225           | 26               |
| 235           | 26               |
| 245           | 26               |



**HDR1**

| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 180           | 16               |
| 190           | 16               |
| 200           | 16               |
| 190           | 20               |
| 200           | 20               |
| 205           | 22               |
| 215           | 22               |
| 225           | 22               |
| 235           | 22               |
| 215           | 26               |
| 225           | 26               |
| 235           | 26               |
| 245           | 26               |



**Scandinavia HD3**



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 210           | 25               |
| 220           | 25               |
| 230           | 25               |
| 240           | 25               |

# Regional

## Retread Product Overview (Continued)

Legend:
 




SmartWay® Verified
 New Tire Available

### Drive Position (continued)



HDW2



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 215           | 27               |
| 225           | 27               |
| 235           | 27               |



HDW2 (Tread B)



| WIDTH<br>(MM)    | DEPTH<br>(32nds) |
|------------------|------------------|
| 245<br>(Tread B) | 27               |

### Trailer Position



Hybrid HT3



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 200           | 16               |
| 210           | 16               |
| 220           | 16               |
| 230           | 16               |



HTR2 SA

| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 250           | 16               |
| 260           | 16               |
| 270           | 16               |
| 290           | 16               |



HTR2



| WIDTH<br>(MM) | DEPTH<br>(32nds) |
|---------------|------------------|
| 290           | 22               |
| 320           | 22               |
| 340           | 22               |

Continental Tire the Americas, LLC  
1830 MacMillan Park Drive  
Fort Mill, SC 29707  
Phone: 704-583-3900  
[www.continental-truck.com](http://www.continental-truck.com)

Technical Customer Services & Warranty  
3000 Continental Parkway  
Clinton, MS 39056  
Phone: 800-726-7113  
[TI\\_CQ\\_SM\\_help.trucktires@continental.com](mailto:TI_CQ_SM_help.trucktires@continental.com)

INSIDE SALES / U.S.  
800-450-4028 East  
800-450-3187 West

Original Equipment Sales  
800-776-2022

Commercial Specialty Tires  
877-235-0102

