

# Conti Coach HA3

## Fuel-Efficient, All-Position Coach

**Noise-reducing tread design**  
for serene and comfortable travel.

**Interlocking 3D sipes**  
provide all-weather traction.



**Intelligent Tire**  
Equipped with TPMS sensor for accurate, realtime tire pressure and temperature readings.

# Conti Coach HA3

## Fuel-Efficient, All-Position Coach

**Extra load-carrying capacity** with a specially reinforced stable bead technology.

Durable casing for **premium retreadability**.

**Noise-reducing tread design** for serene and comfortable travel.

**Interlocking 3D sipes** provide all-weather traction.

### Continental's Intelligent Tire.

- Equipped with TPMS sensor for accurate, realtime tire pressure and temperature readings.
- Sensor warranted for 5 years to minimize disruptions.
- Sensor provides true casing temperature allowing preventive actions that make your tire last longer.
- Avoids valve damage and air leaks by mounting on the inner liner.

Learn more at [www.continental-truck.com](http://www.continental-truck.com). See warranty policy for details.



### Key Features



### Recommended Application

Long Haul Coach



### Compares to

Michelin: X Line Energy Z Coach

## Product Data - Conti Coach HA3

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
315/80R22.5	L	05651710000	17	75	19.7	501	42.4	1077	12.4	315	13.6	345	9.00, 8.25*	13.8	351	488	303	148	67	9090, 130 (4125, 900)	8270, 130 (3750, 900)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

\*315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.