

# Conti EcoPlus HT3

## Fuel-Efficient, Long Haul Trailer

Applications: Trailers and free rolling positions.

Legend:

3G Casing	SmartWay Verified	Intelligent Tire	Retread Available

**PRODUCT FEATURES ABOVE ONLY APPLY TO PRODUCTS IF THE MATCHING ICON IS DARKENED.**

# Conti EcoPlus HT3

## Fuel-Efficient, Long Haul Trailer

GOODS  PEOPLE  CONSTRUCTION



### PRODUCT DATA

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LB	KG
11R22.5	G	05310280000 # 05650960000	13	75	19.2	488	41.2	1046	11.7	297	131	331	8.25, 750	12.5	318	502	312	109	49	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5	H	05310310000 # 05652980000	13	75	19.2	488	41.2	1046	11.7	297	131	331	8.25, 750	12.5	318	502	312	111	50	6610, 120 (3000, 830)	6005, 120 (2725, 830)
255/70R22.5	H	05310340000 # 05651230000	18	75	17.1	434	36.6	929	9.9	251	10.8	274	7.50, 8.25	11.3	287	566	352	93	42	5510, 120 (2500, 830)	5070, 120 (2300, 830)
295/75R22.5	G	05310270000 # 05650910000	13	75	18.5	470	39.7	1008	11.5	292	12.9	328	8.25, 9.00	12.5	318	522	324	104	47	6175, 110 (2800, 760)	5675, 110 (2575, 760)
11R24.5	G	05310260000 # 05651020000	13	75	20.1	511	43.2	1097	11.7	296	131	331	8.25, 750	12.5	318	479	298	117	53	6610, 105 (3000, 720)	6005, 105 (2725, 720)
11R24.5	H	05310350000	13	75	20.1	511	43.2	1097	11.7	296	131	331	8.25, 750	12.5	318	479	298	119	54	7160, 120 (3250, 830)	6610, 120 (3000, 830)
285/75R24.5	G	05310250000	13	75	19.1	485	41.1	1044	11.5	292	12.9	329	8.25	12.5	318	504	313	110	50	6175, 110 (2800, 760)	5675, 110 (2575, 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. # = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

### Features & Benefits



**Advanced tread compound** and optimized tread design provide exceptional mileage.

**Ultra low rolling resistant** trailer tire delivers outstanding fuel efficiency in long haul applications.



Built on the **Conti 3G Casing** for maximum retreadability.



**Improved sidewall construction** for defense against curbing, cuts and abrasions.

**Applications:** Trailers and free rolling positions.