

Conti Hybrid HD3 Super Regional Drive

Applications: Combined long haul highway and regional tandem drive position.

Legend:

3G Casing	SmartWay Verified	Intelligent Tire	Retread Available

PRODUCT FEATURES ABOVE ONLY APPLY TO PRODUCTS IF THE MATCHING ICON IS DARKENED.

Conti Hybrid HD3

Super Regional Drive

GOODS PEOPLE CONSTRUCTION




PRODUCT DATA

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION			
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
11R22.5	G	05210150000 05651760000	27	75	19.7	500	42.0	1067	11.7	296	13.1	331	8.25, 750	12.5	318	493	306	130	59	6175, 105 (2800, 720)	5840, 105 (2650, 720)		
11R22.5	H	05210160000	27	75	19.7	500	42.0	1067	11.7	296	13.1	331	8.25, 750	12.5	318	493	306	132	60	6610, 120 (3000, 830)	6005, 120 (2725, 830)		
295/75R22.5	G	05210170000 05652540000	27	75	19.1	484	40.6	1031	11.7	296	12.7	323	8.25, 900	12.5	318	510	317	123	56	6175, 110 (2800, 760)	5675, 110 (2575, 760)		
11R24.5	H	05210560000	27	75	20.6	522	43.9	1114	11.6	294	13.0	330	8.25, 750	12.5	318	472	293	142	64	7160, 120 (3250, 830)	6610, 120 (3000, 830)		
275/70R22.5* (Tread B)	H	05210920000	22	81	17.6	447	38.3	974	10.9	276	11.3	287	8.25, 750	12.1	307	551	342	115	52	6940, 130 (3150, 900)	6395, 130 (2900, 900)		

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. 0 = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. * - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

Features & Benefits



Fuel-efficient tread compound delivers exceptional rolling resistance balanced with mileage.



Directional tread design with regenerating sipe technologies deliver outstanding traction in tandem axle fitment.



Optimized contour and **balanced footprint distribution** provide extended tread life and premium wear performance.



Built on the **Conti 3G Casing** for maximum retreadability.

Applications: Combined long haul highway and regional tandem drive position.