

Conti Hybrid HS3

19.5" All-Position

Two-layer tread construction

for drivers and combines high mileage performance in the cap compound with significant rolling resistance improvements in the base compound.

Narrowed groove widths

result in increased pattern volume which improves wear resistance to guarantee high mileage performance.



Pocket sipe technology

with full-depth sipes to enhance water displacement and improve wet performance over the life of the tire.

Conti Hybrid HS3

19.5" All-Position

Two-layer tread construction combines high mileage performance in the cap compound with significant rolling resistance improvements in the base compound.



Narrowed groove widths result in increased pattern volume which improves wear resistance to guarantee high mileage performance.

Pocket sipe technology with full-depth sipes to enhance water displacement and improve wet performance over the life of the tire.



Recommended Application

Long Haul and Regional



Compares to

Michelin: Agilis HD Z, X Multi Z | Bridgestone: R238 | Goodyear: Fuel Max RSA ULT

Product Data - Conti Hybrid HS3 (19.5")

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation			
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LB	KG	Single	Dual
																						LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
245/70R19.5	G	05122970000 05654330000	16	81	15.2	386	32.8	833	9.5	241	10.3	262	7.50, 6.75	11.0	279	631	392	78	35	4540, 110 (2060, 760)	4300, 110 (1950, 760)		
245/70R19.5	H	05111130000	16	81	15.2	386	32.8	833	9.5	241	10.3	262	7.50, 6.75	11.0	279	631	392	78	35	4940, 120 (2240, 830)	4675, 120 (2120, 830)		
265/70R19.5	G	05128650000	17	81	15.8	401	34.7	881	10.3	262	10.7	272	7.50, 6.75, 8.25	11.2	286	613	380	82	37	5510, 115 (2500, 790)	4205, 115 (2360, 790)		
285/70R19.5	H	05128630000	18	81	16.2	412	35.9	911	11.1	283	11.6	294	8.25, 7.50, 9.00	12.5	318	590	366	93	42	6610, 125 (3000, 860)	6175, 125 (2800, 860)		

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.