Continental
The Future in Motion

CONSTRUCTION

GOODS PEOPLE CONSTRUCTION

Conti HSC 3

Steer/All-Position

Self-cleaning tread design and groove geometry
for enhanced retreadability and traction.

Intelligent Tire
Equipped with TPMS sensor for accurate, realtime tire pressure and temperature readings.

Maximum sidewall protection
for improved resistance against curbing, cuts and abrasions.

M+S
Mud + Snow Designation

Continental

CONSTRUCTION

Conti HSC 3

Steer/All-Position

Trusted compound technology **delivers up to 10% cut and chip improvement** while maintaining mileage performance.

Built on the innovative **Continental 3G Casing** with premium off-road belt package for maximum retreadability and increased casing life.

Self-cleaning tread design and groove geometry for enhanced retreadability and traction.

Maximum sidewall protection for improved resistance against curbing, cuts and abrasions.

Continental Intelligent Tire.

- Equipped with TPMS sensor for accurate, realtime tire pressure and temperature readings.
- Sensor warrantied for 5 years to minimize disruptions.
- Sensor provides true casing temperature allowing preventive actions that make your tire last longer.
- Avoids valve damage and air leaks by mounting on the inner liner.

Learn more at www.continental-truck.com. See warranty policy for details.



Key Features

M+S
Mud + Snow Designation

Intelligent Tire

3G
3G Casing

Retread Available

Recommended Application

Construction



Compares to

Michelin: X Works Z | Bridgestone: M853 | Goodyear: G751 MSA, Armor Max MSA

Product Data - Conti HSC 3

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
																				Single	Dual
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
11R22.5	H	05652440000	24	68	19.6	498	41.7	1060	11.7	297	12.7	322	8.25, 7.50	12.5	318	496	308	135	61	6610, 120 (3000, 830)	6005, 120 (2725, 830)
12R22.5	H	05652460000	24	68	20.1	512	42.9	1090	11.8	301	13.0	329	9.00, 8.25	13.5	343	482	300	150	68	7390, 120 (3350, 830)	6780, 120 (2725, 830)
315/80R22.5	L	05652480000	24	68	19.8	502	42.9	1089	12.5	318	13.8	351	9.00, 8.25*	13.8	351	483	300	162	74	10200, 130 (4625, 900)	9090, 130 (4125, 900)
11R24.5	H	05652450000	24	68	20.6	523	43.9	1115	11.7	297	12.7	322	8.25, 7.50	12.5	318	472	293	144	65	7160, 120 (3250, 830)	6610, 120 (3000, 830)
12R24.5	H	05652470000	24	68	21.1	537	44.9	1141	12.0	305	14.5	368	9.00, 8.25	13.7	348	461	286	163	74	7830, 120 (3550, 830)	7160, 120 (3250, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

*315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi in dual usage, and 8000 lbs at 120 psi in single usage.

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

03/2025 © Continental Tire the Americas, LLC TT-CO-SS-CHSC3