

Conti HSR 3

Regional All-Position

Zigzag center groove geometry

increases the number of biting edges for increased traction.

Pyramidal stone ejection system

for maximum casing protection.



Applications: Regional hauling and on/off road, all-position.

Conti HSR 3

Regional All-Position

Rigid belt package with full width top belt and extra sidewall protection for increased durability.

Zigzag center groove geometry increases the number of biting edges for increased traction.

Pyramidal stone ejection system for maximum casing protection.

Built on the innovative Conti 3G Casing for **maximum retreadability**.



Key Features

- 3G Casing
- Retread Available
- SmartWay® Verified



Recommended Application

An all-position tire recommended for applications in:
Regional service

Compares to

Michelin: XZE2 | Bridgestone: R250ED | Goodyear: Endurance RSA

Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5	G	05124370000 #05652560000	23	75	19.5	495	41.9	1064	11.6	295	13.0	330	8.25, 7.50	12.5	318	494	307	131	59	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5	H	05124380000 #05652570000	23	75	19.5	495	41.9	1064	11.6	295	13.0	330	8.25, 7.50	12.5	318	494	307	133	60	6610, 120 (3000, 830)	6005, 120 (2725, 830)
11R22.5	H	05124390000 #05652580000	23	75	20.2	513	42.8	1086	11.9	302	13.1	333	9.00, 8.25	13.7	348	484	301	147	67	7390, 120 (3350, 830)	6780, 120 (3075, 830)
295/75R22.5	H	05124410000 #05652600000	23	75	18.9	480	40.2	1022	11.8	299	12.9	328	8.25, 9.00	13.4	340	514	320	127	58	7160, 123 (3250, 850)	6610, 123 (3000, 830)
11R24.5	H	05124430000 #05652620000	23	75	20.5	521	43.8	1113	11.6	295	13.0	330	8.25, 7.50	12.5	318	473	294	143	65	7160, 120 (3250, 830)	6610, 120 (3000, 830)
285/75R24.5	H	05124450000 #05652640000	23	75	19.5	496	41.6	1057	11.8	300	12.9	328	8.25	12.5	318	498	309	133	60	6780, 120 (3075, 830)	6175, 120 (2800, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

PLEASE NOTE: THIS PRODUCT WAS PREVIOUSLY NAMED CONTI CROSSTRAC HA3.

Note - Rim listed first is the measuring rim. #* = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.
- Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.