

# Conti HTL 3

## High Mileage, Long Haul Trailer

Applications: Long haul, over the highway trailer position.

Legend:

|           |                   |                  |                   |
|-----------|-------------------|------------------|-------------------|
|           |                   |                  |                   |
| 3G Casing | SmartWay Verified | Intelligent Tire | Retread Available |

**PRODUCT FEATURES ABOVE ONLY APPLY TO PRODUCTS IF THE MATCHING ICON IS DARKENED.**

# Conti HTL 3

## Long Haul Mileage Trailer

GOODS PEOPLE CONSTRUCTION




| PRODUCT DATA |            |                              |                     |                 |                      |     |                           |      |                        |     |                      |     |                 |                      |     |               |     |             |    |                       |                       |                    |                    |  |  |
|--------------|------------|------------------------------|---------------------|-----------------|----------------------|-----|---------------------------|------|------------------------|-----|----------------------|-----|-----------------|----------------------|-----|---------------|-----|-------------|----|-----------------------|-----------------------|--------------------|--------------------|--|--|
| TIRE SIZE    | LOAD RANGE | ARTICLE NUMBER               | TREAD DEPTH (32nds) | MAX SPEED (MPH) | STATIC LOADED RADIUS |     | OVERALL INFLATED DIAMETER |      | OVERALL INFLATED WIDTH |     | LOADED SECTION WIDTH |     | APPROVED RIM(S) | MINIMUM DUAL SPACING |     | REVS PER UNIT |     | TIRE WEIGHT |    | MAX. LOAD @ INFLATION |                       |                    |                    |  |  |
|              |            |                              |                     |                 | IN                   | MM  | IN                        | MM   | IN                     | MM  | IN                   | MM  |                 | IN                   | MM  | IN            | MM  | MI          | KM | LB                    | KG                    | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |  |  |
| 11R22.5      | G          | 05310820000<br>#05653750000# | 13                  | 75              | 19.2                 | 488 | 41.2                      | 1046 | 11.7                   | 297 | 13.1                 | 333 | 8.25, 7.50      | 12.5                 | 318 | 502           | 312 | 109         | 49 | 6175, 105 (2800, 720) | 5840, 105 (2650, 720) |                    |                    |  |  |
| 295/75R22.5  | G          | 05310830000<br>#05653760000# | 13                  | 75              | 18.5                 | 470 | 39.7                      | 1008 | 11.5                   | 292 | 12.9                 | 328 | 8.25, 9.00      | 12.5                 | 318 | 521           | 324 | 104         | 47 | 6175, 110 (2800, 760) | 5675, 110 (2575, 760) |                    |                    |  |  |
| 11R24.5      | G          | 05310840000<br>#05653770000# | 13                  | 75              | 20.1                 | 511 | 43.2                      | 1097 | 11.7                   | 297 | 13.1                 | 333 | 8.25, 7.50      | 12.5                 | 318 | 479           | 298 | 117         | 53 | 6610, 105 (3000, 720) | 6005, 105 (2725, 720) |                    |                    |  |  |

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. # = Intelligent Tire Article #. \*. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

### Features & Benefits




**Innovative tread compound** delivers improved wear resistance for increased mileage and extended product life.



**Advanced tread** compounding balances cut and tear resistance with optimized rolling resistance satisfying EPA Smartway and CARB requirements.



**Durable sidewall** construction to defend against curbing, cuts and abrasions.



Built on the **Conti 3G Casing** for maximum retreadability.

**High Mileage:**

Improved mileage versus fuel efficient trailer tire Conti EcoPlus HT3.

**Applications:** Trailers and free rolling positions.