

Conti Scandinavia HD3

19.5" All-Season Drive

Deep tread and low void design
ensures long removal miles.

All-season compounding
to deliver performance during any season.



Open shoulder tread design
for increased traction in snow.

M+S

Mud + Snow
Designation

Conti Scandinavia HD3

19.5" All-Season Drive

Deep tread and low void design ensures long removal miles.

Heavy siping provides **numerous gripping edges** for excellent traction on wet roads.

Open shoulder tread design for increased traction in snow.

Increased footprint contact area delivers superior traction and stability.

All-season compound to deliver excellent traction in all weather conditions without sacrificing removal miles.




Key Features

M+S

Mud + Snow Designation Available in 22.5" & 24.5"

Recommended Application

Regional



Compares to

Michelin: XDS 2 | Bridgestone: M704

Product Data - Conti Scandinavia HD3 (19.5")

| Tire Size | Load Range | Article Number | Tread Depth (32nds) | Max Speed (MPH) | Static Loaded Radius | | Overall Inflated Diameter | | Overall Inflated Width | | Loaded Section Width | | Approved Rim(s) | Minimum Dual Spacing | | Revs Per Unit | | Tire Weight | | Max. Load @ Inflation | |
|--|------------|----------------|---------------------|-----------------|----------------------|-----|---------------------------|-----|------------------------|-----|----------------------|-----|-----------------|----------------------|-----|---------------|-----|-------------|----|-----------------------|-----------------------|
| | | | | | IN | MM | IN | MM | IN | MM | IN | MM | | IN | MM | MI | KM | LB | KG | Single | Dual |
| | | | | | | | | | | | | | | | | | | | | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |
| 225/70R19.5 | G | 05230340000 | 19 | 87 | 15.1 | 383 | 32.0 | 813 | 8.6 | 218 | 9.3 | 236 | 6.00, 6.75 | 10.0 | 254 | 647 | 402 | 65 | 30 | 3970, 110 (1800, 760) | 3750, 110 (1700, 760) |
| 245/70R19.5 | H | 05230360000 | 21 | 81 | 15.5 | 394 | 33.3 | 846 | 9.5 | 241 | 10.4 | 264 | 7.50, 6.75 | 11.0 | 279 | 622 | 386 | 80 | 36 | 4940, 120 (2240, 830) | 4675, 120 (2120, 830) |
| TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS | | | | | | | | | | | | | | | | | | | | | |

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.