

Gen 3 Construction Lineup

Conti HSC 3

Intelligent Construction All-Position

Trusted compound technology **delivers up to 10% cut and chip improvement** while maintaining mileage performance.

Built on the innovative Conti 3G Casing **with premium off-road belt package** for maximum retreadability and increased casing life.

Self-cleaning tread design and groove geometry for enhanced retreadability and traction.

Maximum sidewall protection for improved resistance against curbing, cuts, and abrasions.



Key Features



3G Casing




Retread Available



Intelligent Tire



This product has
Mud + Snow designation.



Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	Single	Dual				
																		LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)		
11R22.5	H	005652440000	24	68	19.6	498	41.7	1060	11.7	297	12.7	322	8.25, 7.50	12.5	318	496	308	135	61	6610, 120 (3000, 830)	6005, 120 (2725, 830)
12R22.5	H	005652460000	24	68	20.1	512	42.9	1090	11.8	301	13.0	329	9.00, 8.25	13.5	343	482	300	150	68	7390, 120 (3350, 830)	6780, 120 (2725, 830)
315/80R22.5	L	005652480000	24	68	19.8	502	42.9	1089	12.5	318	13.8	351	9.00, 8.25	13.8	351	483	300	162	74	10200, 130 (4625, 900)	9090, 130 (4125, 900)
11R24.5	H	005652450000	24	68	20.6	523	43.9	1115	11.7	297	12.7	322	8.25, 7.50	12.5	318	472	293	144	65	7160, 120 (3250, 830)	6610, 120 (3000, 830)
12R24.5	H	005652470000	24	68	21.1	537	44.9	1141	12.0	305	14.5	368	9.00, 8.25	13.7	348	461	286	163	74	7830, 120 (3550, 830)	7160, 120 (3250, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

*315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.

Note - Rim listed first is the measuring rim. # = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Conti HAC 3

Intelligent Construction All-Position

Trusted compound technology **delivers up to 10% cut and chip improvement** while maintaining mileage performance.

Self-cleaning tread design and groove geometry for enhanced retreadability and traction.


Rugged 4-belt package resists impacts, bruises, and penetrations for improved casing durability.

Increased sidewall gauge for improved resistance against curbing, cuts, and abrasions.

Key Features



This product has
Mud + Snow designation.



Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
																				LBS, PSI (KG, kPa)	LBS, PSI (KG, kPa)
385/65R22.5	L	05652000000	22	68	19.6	498	42.0	1067	14.8	376	15.9	404	11.75, 12.25	N/A	N/A	493	306	171	78	9920, 130 (4500, 900)	N/A
425/65R22.5	L	05652010000	24	68	20.8	529	44.8	1138	16.6	421	17.9	454	13.00, 12.25, 14.00	N/A	N/A	462	287	190	86	11400, 120 (5150, 830)	N/A
445/65R22.5	M	05652020000	23	68	20.9	531	45.2	1148	17.4	442	18.6	472	13.00, 14.00	N/A	N/A	458	285	210	95	12800, 130 (5800, 900)	N/A
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																					

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Conti HDC 3

Intelligent Construction Drive

Trusted compound technology **delivers up to 10% cut and chip improvement** while maintaining mileage performance.

Wide, aggressive, open shoulder tread design with diamond shaped lugs for excellent traction.

Self-cleaning tread design and miniature stone bumpers reduce stone retention for enhanced retreadability.

Maximum sidewall protection for improved resistance against curbing, cuts, and abrasions.

Key Features



3G Casing




Retread Available



Intelligent Tire



This product has
Mud + Snow designation.



Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
																				LBS, PSI (3000, KPa)	LBS, PSI (3000, KPa)
11R22.5	H	05652410000	30	68	19.9	504	42.1	1069	11.7	298	12.7	322	8.25, 7.50	12.5	318	492	306	143	65	6610, 120 (3000, 830)	6005, 120 (2725, 830)
11R24.5	H	05652430000	30	68	20.7	526	44.1	1120	11.7	298	12.8	324	8.25, 7.50	12.5	318	469	393	153	69	7160, 120 (3250, 830)	6610, 120 (3000, 830)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																					

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. ** = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.
- Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.