

# HCS

## Severe Service All-Position

Outstanding traction, even in harshest terrain, thanks to **tread pattern structure and geometry.**



### **Most durable casing design**

for maximum service life in demanding off-road use, also involving heavy-duty vehicles.

**M+S**

Mud + Snow Designation

# HCS

## Severe Service All-Position

High operational safety, long lasting service and **outstanding resistance to damage through compounds** with extreme resistance to cuts and tears.

Outstanding traction, even in harshest terrain, thanks to **tread pattern structure and geometry**.

**Most durable casing design** for maximum service life in demanding off-road use, also involving heavy-duty vehicles.



### Key Features

M+S



Mud + Snow Designation    Retread Available

### Recommended Application

Off-Road



### Compares to

Michelin: XZL, XZL+ | Bridgestone: L315 | Goodyear: G278 MSD

### Product Data - HCS

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
																				Single	Dual
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
445/65R22.5	L	05160660000 05653580000	27	68	20.9	532	45.5	1156	17.7	449	19.0	482	13.00, 14.00	N/A	N/A	462	287	207	94	12800, 130 (5800, 900)	N/A
325/95R24 (NHS)	H	05160340000	40	50	22.4	568	49.3	1252	12.8	325	13.1	332	8.50, 9.00	14.2	360	430	267	204	92	9370, 120 (4250, 830)	8540, 120 (3875, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE    ■ INTELLIGENT ARTICLE

Note: NHS - Not for Highway Use. Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.

# - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.