

# HDL2

## Fuel-Efficient, Long Haul Drive

**Innovative groove geometry**

minimizes stone retention.



**Advanced tread compounding**

for maximum fuel efficiency.

**Applications: Long haul over the road drive positions.**

# HDL2

## Fuel-Efficient, Long Haul Drive

**Advanced tread compounding** for maximum fuel efficiency.

**Innovative groove geometry** minimizes stone retention.

Built on the Conti 3G Casing for **maximum retreadability**.



### Key Features

**3G**  
3G Casing

SmartWay® Verified



### Recommended Application

A drive tire recommended for applications in:  
**Long Haul service**

### Compares to

Michelin: X Line Energy D+ | Bridgestone: M713 Ecopia | Goodyear: Fuel Max LHD 2

## Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation			
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LB	KG	Single	Dual
																						LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
11R22.5	G	05211220000 #05651770000#	26	75	19.6	499	42.0	1066	11.7	296	13.1	331	8.25, 7.50	12.5	318	493	306	125	57	6175, 105 (2800, 720)	5840, 105 (2650, 720)		
11R22.5	H	05211230000 #05652990000#	26	75	19.6	499	42.0	1066	11.7	296	13.1	331	8.25, 7.50	12.5	318	493	306	128	58	6610, 120 (3000, 830)	6005, 120 (2725, 830)		
11R24.5	G	05211240000	26	75	20.5	521	44.0	1118	11.7	296	13.1	331	8.25, 7.50	12.5	318	470	292	134	61	6610, 105 (3000, 720)	6005, 105 (2725, 720)		

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. # = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.  
# - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.