

HDL2 DL Eco Plus

Fuel-Efficient, Deep Lug Drive

Patented innovative groove technology

leads to minimal stone retention, extending casing life.

Minimized wear and excellent traction over the life of the tire, through a **wide, closed shoulder tread and numerous tread blocks** with multiple grip edges.



32/32" tread depth
provides high mileage and low cost per mile.

HDL2 DL Eco Plus

Fuel-Efficient, Deep Lug Drive

Advanced tread compounding provides this Eco Plus version with 33% less rolling resistance than the original HDL2 DL.

32/32" tread depth provides high mileage and low cost per mile.

Patented innovative groove technology leads to minimal stone retention, extending casing life.

Minimized wear and excellent traction over the life of the tire, through a **wide, closed shoulder tread and numerous tread blocks** with multiple grip edges.

Built on the **Continental 3G Casing** for maximum retreadability.




Key Features

3G
3G Casing SmartWay® Verified

Recommended Application

Long Haul



Compares to

Goodyear: Endurance LHD

Product Data - HDL2 DL Eco Plus

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
11R22.5	G	05211100000 05651850000	32	75	19.7	500	42.2	1071	11.6	294	13.0	329	8.25, 7.50	12.5	318	491	305	132	60	6175, 105 (2800, 720)	5840, 105 (2650, 720)
295/75R22.5	G	05211520000 05654270000	32	75	19.1	485	40.8	1036	11.4	289	12.7	323	8.25, 9.00	12.5	318	507	315	126	57	6175, 110 (2800, 760)	5675, 110 (2575, 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.