

HDO

Off-Road Drive

Deep 32/32" tread

with cut/chip resistant tread provides excellent traction in off-road conditions.



Patented innovative groove technology

leads to minimum stone retention, extending casing life.

M+S

This product is
Mud + Snow Certified.

Applications: Logging, mining, construction and other aggressive, off-road traction needs.

HDO

Off-Road Drive

Deep 32/32" tread with cut/chip resistant tread provides excellent traction in off-road conditions.

Patented innovative groove technology leads to minimum stone retention, extending casing life.

Sidewall profile with curb rib reduces damage from curbing, cuts and abrasions.

Mud & Snow (M+S) certified.



Key Features

M+S

Mud + Snow Certified



Recommended Application

A drive tire recommended for applications in:

Off Road service

Compares to

Michelin: XDY-EX2 | Bridgestone: L317 | Goodyear: G741 MSD

Product Data

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single LBS, PSI (KG, KPa)	Dual LBS, PSI (KG, KPa)
11R22.5	H	05391190000	32	68	19.7	500	42.2	1072	11.0	280	12.0	306	8.25, 7.50	12.5	318	490	305	122	55	6610, 120 (3000, 830)	6005, 120 (2725, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. ♦♦ = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.

- Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.