

♥ GOODS **♥** PEOPLE **♥** CONSTRUCTION

HDR

Fuel-Efficient Drive

Offset center tread blocks

provide excellent all-weather traction.



Tapered tread grooves

reduce stone retention for long casing life and multiple retreads.





HDR

Fuel-Efficient Drive

Multi-service tread compound for local and long haul service.

Offset center tread blocks provide excellent all-weather traction.

Tapered tread grooves reduce stone retention for long casing life and multiple retreads.

Key Features











Recommended Application

Regional and Long Haul

Compares to

Michelin: X Multi D | Bridgestone: M726 | Goodyear: Fuel Max RTD

Product Data - HDR																					
Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
																				Single	Dual
					IN	ММ	IN	ММ	IN	ММ	IN	ММ	Killi(3)	IN	ММ	МІ	км	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
255/70R22.5	Н	05654950000	26	81	17.3	439	37.0	940	10.0	255	10.8	274	8.25, 7.50	11.3	287	559	347	96	44	5510, 120 (2500, 830)	5070, 120 (2300, 830)
							TUBEL	ESS TIF	RESON	15 DEGI	REE DRO	OP CEN	TER RIMS								

■ STANDARD ARTICLE

■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.